

526,789

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 March 2004 (18.03.2004)


PCT

(10) International Publication Number
WO 2004/023608 A1

- (51) International Patent Classification⁷: **H01R 27/00**, 13/627
- (21) International Application Number: **PCT/GB2003/003851**
- (22) International Filing Date: **8 September 2003 (08.09.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data: **0220751.2** **6 September 2002 (06.09.2002)** **GB**
- (71) Applicant (for all designated States except US): **NOKIA CORPORATION** [—/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **BROOKS, Richard** [—/GB]; 11 Lapin Lane, Hatch Warren, Basingstoke, Hampshire RG22 4XH (GB).
- (74) Agents: **SEYMOUR, James et al.**; Nokia IPR department, Nokia House, Summit Avenue, Farnborough, Hampshire GU14 0NG (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: CONNECTOR



(57) Abstract: A connector for coupling a component to external circuitry, comprising a base, a guide for guiding the component along an axis towards the base, a first barb positioned to latch an edge of the component at a first distance along the axis from the base, and a second barb positioned to latch an edge of the component at a second distance along the axis from the base.

WO 2004/023608 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

CONNECTOR

This invention relates to a connector for connecting an electrical component such as a digital camera module to external circuitry.

Background

Digital camera modules have been developed as components for use in electronic apparatus such as personal digital assistants (PDAs) and mobile telephones.

Figures 1 to 4 illustrate such a digital camera module 100. Figure 1 is a perspective top view of the module, Figure 2 is a front side view of the module, Figure 3 is a top plan view of the module, and Figure 4 is a bottom plan view of the module. The module 100 comprises a substrate 110 and a lens structure 130.

The substrate 110 may be a rectangular-shaped ceramic substrate comprising electronic circuitry including an image sensor 116 on a top surface, and metallic terminals 114 on a bottom surface 112 for electrically coupling the module 100 to external circuitry.

The lens structure 130 comprises a rectangular-shaped base portion 135, and a turret portion 150 extending from the base portion 135. The base portion 135 and the turret portion 150 may both be formed of a plastics material. The turret portion 150 defines an aperture 160 through which light is received into the camera module for detection by the image sensor 116. A lens 170 is positioned within the aperture 160 for focusing received light onto the image sensor 116.

A drawback with known digital camera modules is that they are difficult to connect to printed wiring boards (PWBs). Reflow soldering of the ceramic

substrate terminals 114 to a PWB is problematic as the plastics used in the lens 170 melt at temperatures less than the reflow temperatures. Reflow soldering may be possible if the lens is made from a glass material. However, glass lenses are expensive and are less suitable for mass production techniques.

One method for connecting a digital camera module to a PWB involves using a flexible intermediate substrate. The flexible substrate is glued at one end to the bottom surface 112 of the ceramic substrate 110 with locally-conductive adhesive such that the substrate terminals 114 electrically couple to electrical traces in the flexible substrate. The other end of the flexible substrate is then connected to the PWB via a FPC connector. This method is labor intensive and does not lend itself to automated assembly easily.

Summary of the Invention

According to the present invention there is provided a connector for coupling a component to external circuitry, comprising a base, a guide for guiding the component along an axis towards the base, a first barb positioned to latch an edge of the component at a first distance along the axis from the base, and a second barb positioned to latch an edge of the component at a second distance along the axis from the base.

A connector in accordance with the invention has the advantage that it is able to receive components along one axis which in turn enables simple assembly of the component to the connector. A connector in accordance with the invention also has the advantage that it is able to receive components that have housings of different height due to the two barb arrangement. In other words, the two barb arrangement enables a component to be retained by an edge of the component even when the height of that edge varies.

The component is preferably a digital camera module.

Suitably, the base includes electrical interconnects for coupling to the component/digital camera module.

Preferably, the guide comprises side walls extending from a planar base.

Embodiments of the invention will now be described in more detail, by way of example, with reference to the enclosed drawings, in which:

Figure 1 is a perspective top view of a camera module;

Figure 2 is a front side view of the module;

Figure 3 is a top plan view of the module;

Figure 4 is a bottom plan view of the module;

Figure 5 is a plan view of a connector in accordance with the invention;

Figures 6 and 7 are side views of the connector and the module;

Figure 8 is a cross-sectional side view of the connector illustrating the position of retaining barbs;

Figure 9 is side view of two barbs;

Figures 10 and 11 are schematic side views of the two barbs operating against a camera module; and

Figures 12 to 17 are schematic side views of the four barbs of Figure 8 operating against a camera module.

Description of a Preferred Embodiment

Figure 5 is a plan view of a connector 200 in accordance with the invention. The connector is made of a plastics material and is shaped generally like box having an open top. The connector 200 is further illustrated in Figures 6 and 7, which show a side view and an end view respectively.

The connector 200 comprises a generally planar base portion 220 and four side walls 210 extending perpendicular to the base to form the open box shape.

As shown in Figure 6, the connector 200 is designed to receive the camera module 100 of Figure 1 along the Z-axis. Eight electrical interconnects 230 made of metal such as copper are embedded into the base 220 such that each interconnect has a internal portion extending to the inside of the box, and a external portion extending to the outside of the box. The internal portions are designed to couple to the terminals 114 of the camera module once it has been fully inserted into the connector 200. The external portions are designed to be soldered to traces of a PWB (not shown) in order to provide electrical connections to external components. The connector 200 is preferably reflow soldered to the PWB before the camera module 100 is received into the connector. Other types of connection between the external portions and the PWB may also be used, such as pin and socket type connections.

In an alternative embodiment, the internal portions of the interconnects may extend up the side walls 210 to couple with correspondingly positioned terminals on the camera module.

As shown in Figures 4 and 5, the external dimensions x_1 and y_1 of the rectangular-shaped base portion 135 of the camera module 100 are slightly smaller than the internal dimensions x_2 and y_2 of the connector box opening

defined by the side walls 210. The side walls 210 thus act as guides to guide the camera module 100 into the connector along the Z-axis.

It is important that the camera is held in the connector so that the terminals 114 remain coupled to the interconnects 230. Figure 8 illustrates the barbs that form part of the connector 200 to achieve this function. The barbs need not be exactly the pointed shape illustrated in the Figures so long as they function to hold the camera module at the desired position. Accordingly, the term barb is intended to encompass more rounded shapes than those illustrated.

Figures 8 and 12 to 17 illustrate an embodiment of the connector with four barbs 241, 242, 243, 244. An alternative embodiment of the connector with just two barbs is illustrated in Figures 9 to 11. The barbs are supported by arms 251-254 that extend from the base 220 of the connector. The arms are coupled to the base 220 such that they can move independently of each other. Recesses 270 in the side walls 210 allow the arms and barbs to spring back as the camera module is received into the connector 200.

In Figure 8, the two lower barbs 243, 244 of the of four barbs are positioned at a distance H1 from the base 220, while the two upper barbs 241, 242 are positioned at a distance H2 from the base 220.

The height of the camera module H3 (see Fig. 2) is known to have a large tolerance due to variations in the alignment of the lens structure 130 to the substrate 110. The use of barbs at different heights enables the connector 200 to receive and retain camera modules that vary greatly in height. Preferably the upper barb is positioned at a height H2 that is near the maximum tolerance for H3 while the lower barb is positioned at a height H1 that is near the minimum tolerance for H3.

Figure 11 illustrates how the connector 200 according to the invention can retain a camera module 100 that has a large height $H3$ by means of the upper barb 261. The lower barb 262 is simply deflected out of the way. Figure 10 in contrast illustrates how the connector 200 according to the invention can retain a camera module that has a smaller height $H3$ by means of the lower barb 262.

Figures 12 to 15 illustrate the sequence of deflections of the four barbs 241-244 (originally shown in Figure 8) as a camera module 100 with a small height is received by the connector 200 along the vertical z -axis. Figures 16 and 17 illustrate a similar sequence for a camera module 100 with a larger height. Figures 15 and 17 illustrate the camera module 100 fully inserted and retained in the connector 200.

In accordance with the invention, further barbs may be added at heights other than $H1$ and $H2$ to accommodate further variations in the height $H3$ of the camera module, or to engage different edges of the camera module.

Other components that may be retained by the connector include, for example, lamps, laser diodes etc.

Claims:

1. A connector for coupling a component to external circuitry, comprising a base, a guide for guiding the component along an axis towards the base, a first barb positioned to latch an edge of the component at a first distance along the axis from the base, and a second barb positioned to latch an edge of the component at a second distance along the axis from the base.
2. A connector as claimed in claim 1, wherein the component is a digital camera module.
3. A connector as claimed in claim 1 or 2, wherein the base includes electrical interconnects for coupling to the component.
4. A connector as claimed in claim 1, 2 or 3, wherein the guide comprises side walls extending from the base.
5. A connector as claimed in any one of claims 1 to 4, wherein the base is generally planar.

1 / 9




FIG. 1




FIG. 2




FIG. 3

2 / 9




FIG. 4




FIG. 5

3 / 9




FIG. 6












FIG. 7







7 / 9





9 / 9



INTERNATIONAL SEARCH REPORT

In Application No

PCT/GB 03/03851

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H01R27/00 H01R13/627

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01R H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 302 141 A (SCRIBNER DANA P ET AL) 12 April 1994 (1994-04-12) abstract	1
A	US 6 078 756 A (ALLEN JAMES D ET AL) 20 June 2000 (2000-06-20)	
A	US 2002/101534 A1 (LIU ANDREW) 1 August 2002 (2002-08-01)	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

28 November 2003

Date of mailing of the international search report

04/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Bertin, M

INTERNATIONAL SEARCH REPORT

Application No
PCT/GB 03/03851

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5302141	A	12-04-1994	NONE	
US 6078756	A	20-06-2000	NONE	
US 2002101534	A1	01-08-2002	TW 460005 Y	11-10-2001